

030 : WATER TREATMENT & BLEACHING AGENT

DESCRIPTION: 030 is a concentrated oxygen bleach source in convenient liquid form. 030, when properly applied will provide protection against excessive odor and fouling of water wash and rinse solutions under recirculated conditions. Some typical uses for 030 include shock treatment for biologically fouled cooling towers, or as an additive to recirculated wash and rinse solutions (such as car washing operations). There are no odor, toxic, or contamination problems when using 030 as the only decomposition products are oxygen and water. Use of 030 significantly extends the useful detergent tank life, while preventing biological fouling. 030 should be added by means of a low volume chemical proportioning pump, and calibrated for use level by infrequent titration in order to insure adequate levels of available oxygen for proper performance.

PRODUCT PROPERTIES:

Appearance: Clear liquid, odor nil.

Specific Gravity: 1.13

Solubility: Complete

Flash Point: None

pH(1%): 5.0-6.0

Phosphate Content: None

USE INFORMATION:

Concentration: 1 pint per 100 gallons of water = 200 ppm as oxygen

Temperature: Ambient to 120°F.

Contact Time: As available

PRECAUTIONS: May cause irritation to the eyes upon contact. ****AVOID CONTACT****
Prolonged contact may cause skin irritation. When handling, wear proper personal protective equipment as indicated by the accompanying OSHA material safety data sheet. If accidental contact is made immediately flush contacted area repeatedly with cool water. If irritation persists call a physician for treatment. If accidental eye contact occurs flush eyes with cool water and seek the immediate attention of a physician. Launder contaminated clothing before re-use. Wash thoroughly after handling. **FOR INDUSTRIAL & COMMERCIAL USE ONLY!**

PACKAGE: 55, 30, 15, 5, 4x1 gal.

Issue date: 1/17/12