

540: LIQUID OXYGEN SCAVENGER BOILER ADDITIVE

DESCRIPTION: 540 is a highly concentrated cobalt catalyzed liquid boiler additive which controls dissolved oxygen in boiler feed waters, which is a major source of corrosion on internal boiler components. Noticeable corrosion may occur where the dissolved oxygen level is greater than 0.01ppm. For this reason a sulfite residual is recommended even if a deaerator is present.

PRODUCT PROPERTIES:

Appearance: Clear amber liquid, odor nil.

Specific Gravity: 1.10

Solubility: Complete

Flash Point: None

pH(1%): 8.0

Phosphate Content: None

USE INFORMATION:

Concentration: Maintain 20-40ppm as sulfite , 1 pint/1000gal = 100ppm

PRECAUTIONS: May cause irritation to the eyes upon contact. ****AVOID CONTACT**** Prolonged contact may cause skin irritation. When handling, wear proper personal protective equipment as indicated by the accompanying OSHA material safety data sheet. If accidental contact is made immediately flush contacted area repeatedly with cool water. If irritation persists call a physician for treatment. If accidental eye contact occurs flush eyes with cool water and seek the immediate attention of a physician. Launder contaminated clothing before re-use. Wash thoroughly after handling.

FOR INDUSTRIAL & COMMERCIAL USE ONLY!

PACKAGE: 55, 30, 15, 5, 4x1gal.

Issue date : 1/17/12